

EVO® 6161 Full Brim Unvented Wheel Ratchet Hard Hat

White / AJP170-000-1AN



DESCRIPTION

The EVO® 6161 Full Brim hard hat combines a super strong HDPE shell with the comfort benefits of the Evolution® 3D-Adjustment™ harness system.

SAFETY STANDARDS

- AS/NZS 1801
- ANSI/ISEA Z89.1 Type I

FEATURES

- The EVO® 6161 outperforms ANSI/ISEA Z89.1 Type I standard requirements, delivering optimum performance in today's advanced environment.
- 6-point textile cradle suspension system and Chamlon™ sweatband offer unrivalled comfort.
- Strengthen your corporate identity by applying a company logo on the front or side of this hard hat. Minimum order quantities and set-up charges apply.
- Assembly kit available separately for adding a clear or shaded polycarbonate retractable eyeshield to an existing EVO® 6161 Full Brim hard hat. Tested to ANSI/ISEA Z87.1.
- Optional high intensity CR2 reflective tape for added visibility.

SPECIFICATIONS

	Peak Full Brim		Impact Grade 50 Joules
	EN 50365 ELECTRICAL INSULATION 1000v		ANSI Electrical Class E Yes
	Lateral Deformation No		Maximum Temperature +50°C
	Resistance to Molten Metals and Hot Solids Helmets (optional) Yes		HDPE Shell Yes
	Minimum Temperature -40°C		Textile Harness
	Recyclable Shell		Wheel Ratchet Yes
	Depth Adjustment 3D Harness		Reflective Option Optional
	Ventilation No		ID card holder Optional
	Integrated Eyewear Optional		Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional
	BSI Kitemark Yes		JSPCheck Yes
	Optional 4 point chinstrap (EN397 Compliant) Optional		Size 53-64cm
	Product Weight 428g		

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Construction and Infrastructure

Oil, Gas and Chemical Companies

Renewable, Wind and Solar Energy

Mining, Aggregates and Quarrying

Rail and Tunnelling

Utilities Contractors