

POWERSOFT™ MEGA T-FIT™

**CLASS 4 EARPLUGS | UNCORDED |
CORDED | DISPENSER**



PRODUCT CODE: 267-HPF510 | 267-HPF510C | 267-HPF510-1 | EPDS500A

**MEGA
T-FIT™**

PowerSoft™
FOAM TECHNOLOGY



267-HPF510



267-HPF510C



267-HPF510-1



EPDS500A

FEATURES

- » Innovative "T-shape" makes fitting and removal simple
- » PowerSoft™ foam technology delivers optimal expansion recovery time for a consistent, uniform fit
- » High level comfort and noise reduction protection you can rely on
- » Smooth closed cell outer layer that reduces surface contamination
- » Soft and comfortable PowerSoft™ foam supports all day comfort

Ear Plug Dispenser:

- » Dispenser holds 500 pairs of PowerSoft™ Mega T-Fit™ Uncorded Earplugs
- » Dispenses one pair at a time

SPECIFICATIONS

Material: PU Foam

Length: 25mm

Width: 11.3mm

Corded Length: 620mm

Weight: 0.5g

Colour: Hi-Vis Orange

APPLICATIONS

- » Agriculture
- » Aviation
- » Automotive
- » Chemical Manufacturing
- » Construction
- » Forestry
- » Heavy Engineering
- » Metal Processing
- » Mining and Quarrying
- » Welding
- » Woodworking

PACKAGING

267-HPF510 (Uncorded)

Unit: 200 Pairs (1 Box) | **Carton:** 10 Boxes

267-HPF510C (Corded)

Unit: 100 Pairs (1 Box) | **Carton:** 10 Boxes

267-HPF510-1 (Uncorded Dispenser Refill)

Unit: 250 Pairs (1 Box) | **Carton:** 10 Boxes

EPDS500A (Dispenser)

Unit: 1 Dispenser | **Carton:** 5 Dispensers

CARE INSTRUCTIONS

These ear plugs are disposable, but when not in use should be kept in clean, dry conditions.

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
FREQUENCY HZ	125	250	500	1000	2000	4000	8000
MEAN ATTENUATION	22.8	21.4	23.7	25.3	34.3	41.6	41.4
STANDARD DEVIATION	7.3	7.6	8.3	7.6	5.5	4.5	6.5
MEAN-MINUS-STANDARD DEVIATION ATTENUATIONS	15.5	13.8	15.4	17.7	28.8	37.1	34.9

SLC₈₀ Value is 22dB (Class 4)

STANDARDS



PC10236
AS/NZS 1270:2002



PIP ANZ (AUSTRALIA
& NEW ZEALAND)

AUSTRALIA
PHONE: 1300 747 269

NEW ZEALAND
PHONE: 0800 747 269

info@pipanz.com
www.pipanz.com

PIP
GLOBAL SAFETY