

POWERSOFT™ MEGA T-FIT™

CLASS 4 EARPLUGS | UNCORDED | CORDED

PRODUCT CODE: 267-HPF510 | 267-HPF510C | 267-HPF510-1



PowerSoft™
FOAM TECHNOLOGY

MEGA
T-FIT™



267-HPF510



267-HPF510C



267-HPF510-1

FEATURES

- » Innovative "T-shape" makes fitting and removal simple
- » PowerSoft™ foam technology delivers optimal expansion recovery time for a consistent, uniform fit
- » High level comfort and noise reduction protection you can rely on
- » Smooth closed cell outer layer that reduces surface contamination
- » Soft and comfortable PowerSoft™ foam supports all day comfort
- » Earplug Dispenser available separately (EPDS500A)

SPECIFICATIONS

Material: PU Foam
Length: 25mm
Width: 11.3mm
Corded Length: 620mm
Weight: 0.5g
Colour: Hi-Vis Orange

APPLICATIONS

- » Agriculture
- » Aviation
- » Automotive
- » Chemical Manufacturing
- » Construction
- » Forestry
- » Heavy Engineering
- » Metal Processing
- » Mining and Quarrying
- » Welding
- » Woodworking

PACKAGING

267-HPF510 (Uncorded)

Unit: 200 Pairs (1 Box) | **Carton:** 10 Boxes

267-HPF510C (Corded)

Unit: 100 Pairs (1 Box) | **Carton:** 10 Boxes

267-HPF510-1 (Uncorded Dispenser Refill)

Unit: 250 Pairs (1 Box) | **Carton:** 10 Boxes

CARE INSTRUCTIONS

These ear plugs are disposable, but when not in use should be kept in clean, dry conditions.

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
FREQUENCY HZ	125	250	500	1000	2000	4000	8000
MEAN ATTENUATION	22.8	21.4	23.7	25.3	34.3	41.6	41.4
STANDARD DEVIATION	7.3	7.6	8.3	7.6	5.5	4.5	6.5
MEAN-MINUS-STANDARD DEVIATION ATTENUATIONS	15.5	13.8	15.4	17.7	28.8	37.1	34.9

SLC₈₀ Value is 22dB (Class 4)

STANDARDS



PC10236
AS/NZS 1270:2002