

VERISHIELD™ DIELECTRIC VS100DH PASSIVE HELMET EARMUFF

PRODUCT CODE: 1035203-VS



Hard Hat Adapters



3713VS1



3714VS1



3718VS1

FEATURES

- Fits a wide range of head sizes comfortably
- Wide ear cup opening suits larger ears and hearing aids
- Memory foam ear cushions for enhanced comfort and attenuation
- ABS molded construction with internal baffle design for reduced weight
- Oil-resistant cup surface ideal for heavy-duty environments
- Air Flow Control technology delivers high attenuation without extra bulk
- Optimised internal airflow design improves consistent noise reduction
- The dielectric construction is suitable for all workplaces, especially electrical environments
- Attenuation level marked on cup for quick on-site identification
- Supplied with three attachment styles, including 3713VS1, 3714VS1 and 3718VS1, to suit a variety of compatible hard hats

SPECIFICATIONS

Attenuation Type: Passive

Noise Environment: Medium/High

Cup Material: PVC/PU Foam/ABS

Operating Temperature Range: 0°C to +55°C

Weight: 317g

Colour: Black

Country of Origin: China

APPLICATIONS

Recommended for use in the following applications:

- Construction
- Manufacturing
- Forestry
- Oil and Gas
- Electrical Maintenance and Arc-Flash Risk Areas
- Utilities
- DIY

PACKAGING

Unit: 1 | **Carton:** 10

TEST DATA

ATTENUATION TABLE (dB)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	12.6	14.7	21.4	23.2	29.9	34.9	34.6
Standard Deviation	4.7	4.7	4.7	3.2	4.2	4.0	4.2
Mean-Minus-Standard Deviation Attenuations	7.9	10.0	16.7	20.0	25.7	30.9	30.4

SLC₈₀ Value is 22 (Class 4)

STANDARDS

AS/NZS 1270:2002 Acoustic Hearing Protectors -
Class 4 SLC₈₀ 22dB



AS/NZS 1270:2002
SAI Global
SMK 1133/1



PIP ANZ (AUSTRALIA
& NEW ZEALAND)

AUSTRALIA
PHONE: 1300 747 269

NEW ZEALAND
PHONE: 0800 747 269

info@pipanz.com
www.pipanz.com

PIP
GLOBAL SAFETY