



KMAX.1 Welder's Cross-over Style Harness

Product description

The KMAX harness has been designed for use in applications where hot sparks or molten materials may come into contact with the harness.

FEATURES

- Frontal d-ring for frontal fall arrest.
- Rear fall arrest d-ring.
- Specialised KEVLAR™ webbing for protection from sparks and molten material.
- Kevlar™ webbing resistant to high temperatures.
- Equipped with a label pack housing all relevant harness information including donning instructions, connection instructions, AS/NZS 1891.12007 certification and inspection grid. The label pack is also equipped with an oversized pullfree lanyard ring enabling the user to temporarily park the lanyard.
- Fully adjustable leg straps.
- All attachment points are clearly labelled and define the application of the attachment.

APPLICATIONS

- Welding at height
- Grinding at height
- Harsh work environments

Technical Information

- Manufactured from heavy duty 100% Kevlar™
- Weight 1.2kg

STANDARDS

- Certified to Australian and New Zealand Standard AS/NZS 1891.1 - 2007.

ORDERING DETAILS

ATTACHMENT POINTS											
PART NO.	DESCRIPTION	REAR	FRONTAL	CONFINED SPACE	WORK POSITIONING	EXTEND DEE	SIZE	MIN QTY	CAT	PACKAGE DIMENSIONS	BARCODE
M1020066	KMAX.1 welder's harness	Y	Y	N	N	N	M	1	A	360 x 322 x 105	9333633009135

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM PIP GLOBAL SAFETY AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. PIP GLOBAL SAFETY RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

AUSTRALIA AND NEW ZEALAND
For More Information
www.pipglobalsafety.com | [Contact us](#)

PIP
GLOBAL SAFETY