



Fall Arrest Harness

Product description

The Fall Arrest Harness is suitable for any general working at height application. The highly visible polyester webbing makes it easy to detect worker compliance. It is a light-weight harness which makes it comfortable to wear all day long with minimal restriction to the wearer's movements.

FEATURES

- Frontal belay loops for fall arrest (must be used together).
- Large rear fall arrest d-ring.
- Push-through alloy steel buckles.
- Vest style makes it easy to don.
- Fully adjustable:
 - chest strap
 - shoulder
 - leg straps
- All attachment points are clearly labelled and define the attachment's application.
- Brightly coloured webbing enables the user to be easily identified whilst working at heights.
- Webbing has excellent UV resistant properties.



APPLICATIONS

- Construction & Maintenance
- Scaffolding
- Warehousing
- Roof work
- General working at height application

Technical Information

- Manufactured from heavy duty and light-weight 43mm polyester webbing.
- Hardware: zinc plated alloy steel
- Weight 1 kg

STANDARDS

Certified to Australian and New Zealand Standard AS/NZS 1891.1- 2007.

ORDERING DETAILS

ATTACHMENT POINTS											
PART NO.	DESCRIPTION	REAR	FRONTAL	CONFINED SPACE	WORK POSITIONING	EXTEND DEE	SIZE	MIN QTY	CAT	PACKAGE DIMENSIONS	BARCODE
M1020250	Fall arrest harness	Y	Y	Y	N	N	Universal	1	A	360 x 322 x 105	9333633013989

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM PIP GLOBAL SAFETY AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. PIP GLOBAL SAFETY RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

AUSTRALIA AND NEW ZEALAND
For More Information
www.pipglobalsafety.com | [Contact us](#)

PIP
GLOBAL SAFETY