



MILLER® Bandit Tool Strap and Hand Tool Strap

Product description

Tool straps and lanyards are used to attach tools when working at height and prevent tools from accidentally falling to the ground.

FEATURES

Bandit Tool Strap

- Bandit tool strap conveniently attaches to the user's belt.
- Tool attachment is via a small karabiner or the adjustable clinching cord.
- Elasticised cord for greater worker flexibility.
- 660mm when retracted and 1900mm when fully extended.
- Will hold a tool with a maximum weight of 2.26kg.

Hand Tool Strap

- Allows the worker to attach a tool to one end and have the other end attached to the wrist.
- Light-weight webbing with cord for wrapping around tools.
- Adjustable wrist strap to suit the user.
- 1100mm long.
- Will hold a maximum tool weight of 5kg.



Bandit Tool



Hand Tool

APPLICATIONS

- Work at height
- Maintenance
- Construction
- Building
- Roof Work
- Scaffolding

ORDERING DETAILS

PART NO.	DESCRIPTION	MIN QTY	CAT	MAX WEIGHT TOOL	PACKAGE DIMENSIONS	WEIGHT	BARCODE
9077	Bandit Tool Strap	1	A	2.26kg	230 × 70 × 40	92g	612230118266
TL15	Hand Tool Strap 1.1m	1	A	5kg	320 × 220 × 40	100g	9333633003423
M1020115	Hand Tool Strap 500mm	1	A	5kg	195 × 130	35g	9333633010407

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM PIP GLOBAL SAFETY AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. OUR COMPANY RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Australia and New Zealand

For More Information

www.pipglobalsafety.com | [Contact us](#)

PIP
GLOBAL SAFETY