



KMAX Welder's Vest Style Harness

Product description

The KMAX.3 Welder's Vest Style harness has been designed for use in applications where hot sparks or molten materials may come into contact with the harness.

FEATURES

- Frontal d-ring for fall arrest.
- Rear fall arrest d-ring.
- Manufactured from specialized Flame Resistant
- KEVLAR® webbing. Kevlar® material provides resistance to high temperatures.
- Equipped with a label pack housing all relevant harness information including donning instructions, connection instructions, AS/NZS 1891.1:2007 certifications and inspection grid. The label pack is also equipped with an oversized pullfree lanyard ring enabling the user to temporarily park the lanyard.
- Fully adjustable leg and shoulder straps.
- All attachment points are clearly labelled and define the attachment's application.

APPLICATIONS

- Welding at height
- Grinding at height
- Harsh work environments

ORDERING DETAILS

PART NO.	DESCRIPTION	ATTACHMENT POINTS					SIZE	MIN QTY	CAT	PACKAGE DIMENSIONS	BARCODE
		REAR	FRONTAL	CONFINED SPACE	WORK POSITIONING	EXTEND DEE					
M1020100	KMAX.3 welder's vest style harness	Y	Y	N	N	N	M	1	A	360 x 322 x 105	9333633010162
M1020102	KMAX.3 welder's vest style harness	Y	Y	Y	Y	Y	M	1	A	360 x 322 x 105	9333633010131

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM PIP GLOBAL SAFETY AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. PIP GLOBAL SAFETY RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

AUSTRALIA AND NEW ZEALAND
For More Information
www.pipglobalsafety.com | [Contact us](#)

PIP
GLOBAL SAFETY