



Adjustable Welder's Lanyard

Product description

The KMAX flame-resistant adjustable lanyard is designed for applications where hot sparks or molten materials may contact the lanyard.

FEATURES

- 2m shock-absorbing lanyard with 19mm double-action hooks at each end.
- Integral compact energy absorber provides smoother shock absorption.
- Kevlar® webbing offers heat resistance and durability in harsh environments.
- Adjustable length from 600mm to 2m.
- Includes label with all relevant information such as connection instructions and AS/NZS 1891.1:2007 certification.

APPLICATIONS

- Welding at height.
- Grinding at height.
- Harsh work environments.



TECHNICAL DETAILS

- Manufactured from heavy-duty 43mm Kevlar® webbing.
- Weight: 1.3 kg.

STANDARDS

Certified to AS/NZS 1891.1:2007.

ORDERING DETAILS

PART NO.	DESCRIPTION	STYLE	MATERIAL	LENGTH	TERMINATIONS	MIN QTY	CAT	PACKAGE DIMENSIONS	BARCODE
LA11KEC2.0	KMAX adjustable lanyard	Adjustable	Kevlar	2m	19mm hook e/end	1	A	410 x 240 x 55	9333633010131

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM PIP GLOBAL SAFETY AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. OUR COMPANY RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Australia and New Zealand
For More Information
www.pipglobalsafety.com | [Contact us](#)

