

PASSIVE SLIMLINE EARMUFFS FOR USE WITH THE VANGUARD G4 PAPR

PRODUCT CODE: PRH-G4-PCEM

Slimline and easy-to-mount to the Vanguard G4 PAPR helmet using a robust military-style slide system, these earmuffs deliver Class 5 hearing protection (SLC_{80} 32 dB) in a lightweight, ergonomic design.

FEATURES

- » SLC_{80} 30dB, Class 5
- » Easy-to-mount military-style slide system
- » Lightweight, ergonomic design with soft ear cushions
- » Slimline design

SPECIFICATIONS

- » **Materials:** Stainless Steel, ABS, PU Foam, PVC
- » **Weight:** 251 grams

PACKAGING

Unit: 1 | Carton: 10

APPLICATIONS

- » Designed for use in noisy environments such as Agriculture, Construction, Energy, Industrial, Mining, Oil & Gas, Painting, Healthcare, Pharmaceuticals, Welding, Grinding & Sanding

TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
FREQUENCY HZ	125	250	500	1000	2000	4000	8000
MEAN ATTENUATION	18.5	21	27.3	36.4	37.8	39.1	39.1
STANDARD DEVIATION	4	3.2	3.3	4.4	4	3.8	4.8
MEAN-MINUS-STANDARD DEVIATION ATTENUATIONS	14.5	17.8	24	32	33.8	35.3	34.3

SLC_{80} Value is 30dB (Class 5)



CARE INSTRUCTIONS

- » Inspect earmuffs for wear and tear before use.
- » **Storage:** Store the earmuffs in a dry and well ventilated location when not in use. Avoid exposure to hot or humid environments, as this may lead to damage.
- » **Cleaning:** After use, wipe clean with a damp cloth and mild detergent. Do not use strong chemicals or abrasive cleaners. Do not immerse in water.
- » **Maintenance:** Replace earmuffs if they are damaged or cannot be cleaned. Do not continue using damaged earmuffs.
- » **Operating Temperature:** 4°F (-20°C) to 131°F (55°C)
- » **Storage Temperature:** -4°F (-20°C) to 131°F (55°C)

STANDARDS

- » Compliant with AS/NZS 1270 Acoustic Hearing Protectors.