



PRODUCT DESCRIPTION

The SYNERGY blends style and function with an ultra-lightweight, comfortable fit. Its ergonomic polycarbonate frame is strong, durable, metal-free, and 100% recyclable. The optically correct single-piece lens features full Titanium Anti-Fog and Anti-Scratch coating for consistently clear, razor-sharp vision.

- Ultra lightweight
- One piece, distortion free moulded lens
- Moulded PVC nose bridge
- Dielectric design contains no metal parts
- Fully recyclable all polycarbonate frame



AUSTRALIAN STANDARD
AS/NZS 1337.1:2010
SAI GLOBAL LIC 40211

PRODUCT RANGE



600_C



600_S



600_CP

Product Code	Frame Colour	Temple Colour	Lens Type	Lens	Lens Coating	Filters	Lens Marking
600_C	Clear	Clear	Standard	Clear	Titanium Anti-Fog/Anti-Scratch	UV400	I0
600_S	Smoke	Smoke	Standard	Smoke	Titanium Anti-Fog/Anti-Scratch	UV400	I3
600_CP	Copper	Copper	Standard	Copper	Titanium Anti-Fog/Anti-Scratch	UV400	I2

SPECIFICATIONS

Lens	9 base curve
Frame	Polycarbonate
Weight	25 grams
Nose Piece	PVC
Country of Origin	Taiwan

PACKAGING

Polybag: 1 pair

Inner Box: 10 pairs

Outer Carton: 200 pairs

CLEANING AND STORAGE

Clean lenses regularly with mild soapy water or Scope Aquaclean Plus range:

- **AC500:** 500 pre-moistened towelettes
- **AC100:** 100 pre-moistened towelettes
- **AC500CS:** Cleaning station (spray bottle + tissues).

Do not use alcohol/ammonia/propane based cleaners.

Store in pouch or case in a clean, dry environment.

STANDARDS

AS/NZS 13371:2010 – Medium Impact Protection

MARKING EXPLANATION

Impact Resistance

All Scope safety eyewear complies to AS/NZS 13371 2010 Medium Impact Protection and are marked by the letter "I" on the lens.

Outdoor Untinted

These lenses are intended for outdoor and indoor use where no optical radiation hazards exist other than solar radiation. They are intended to provide adequate protection against UV radiation from the sun, but are not intended to provide protection against sunglare.

Lens Marking: I0

Outdoor Tinted

These eye protectors are intended for outdoor use where no optical radiation hazards exist other than solar radiation. They are intended to provide adequate protection against sun glare and ultraviolet radiation from the sun.

Lens Marking: I1, I2, or I3